

HOFMANN®



monty™ 4400

TIRE CHANGER

monty™ 4400

Make wheel service for trucks, tractors, off-road and skidder wheels a faster, easier and more profitable part of your business with Hofmann's monty 4400. This heavy-duty tire changer is designed to mount/demount tires up to 90" in diameter. The monty 4400 features a hydraulically-operated self-centering four jaw chuck with clamping jaws that can clamp from 14" - 44" either from the wheel inside or from the wheel center bore. It also has one-operator capability that allows one person to safely monitor all tire-changing operations. The bead breaker disc and mount/demount heads are combined into one assembly for ease-of-use. This mount/demount head is manually operated on the monty 4400.

Four Jaw Clamping Chuck

These self-centering hydraulically-operated clamping jaws can clamp from 14" - 44" either from the inside of the wheel or the wheel's center bore. Optional jaw extensions increase clamping range to 56".

One-Man Operation

The remote control console allows one person to safely monitor all tire changing operations.

Patented Mount/Demount Head Assembly

The bead breaker disc and mount/demount heads are combined into one assembly for ease-of-use. This mount/demount head is manually operated on the monty 4400.

Versatility

The 3 HP 2 speed bi-directional chuck motor and heavy-duty hydraulics allow the monty 4400 to handle the toughest tubeless, tube type, single or multi-piece, Budd, and Dayton wheels.

TIRE CHANGER

Specifications

Wheel Width:	14" - 44"
Max. Wheel Assembly Width:	90.5"
Max. Wheel Width:	43"
Hydraulic Motor:	2 HP
Chuck Motor:	3 HP
Chuck Spindle Diameter:	5"
Rotational Torque:	2,268 ft. lbs.
Dimensions (WxDxH):	81" x 117" x 63"
Shipping Weight:	2,085 lbs.
Power Requirements:	200/230V, 3Ph, 50/60 Hz

Standard Accessories

EAA0247G02A	Tire lever
ST4004461	Large bead lifting lever
ST4002354	Bead mounting lever
ST401914	Alloy jaw protectors
EAA0329G10A	Wheel clamp pliers

Optional Accessories

ST4019161	Jaw extensions (up to 56")
ST4022287	Bead roller
ST4021852	Alloy wheel clamp
ST4008257	Protective alloy jaws
RTT75	Standard paste
RTT75N	Low Profile Paste

Hofmann manufactures a complete line of wheel service equipment.



Combination brake lathes for rotors, drums and flywheels



Portable Imaging Alignment Systems



14,000 lb. Capacity Scissor Alignment Lifts



USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

HOFMANN®

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca

