




JWDS-2550 DRUM SANDER WITH OPEN STAND

723550OSK

Introducing the new JWDS-2550 Drum Sander from JET. The 1.75 horsepower motor delivers plenty of power to handle just about any sanding task. The innovative tool-less parallelism system keeps adjustments simple. The worktable is easily positioned by a turn of the parallelism dial. The variable-speed rate permits you to choose the optimal feed rate for a full range of projects, while the Sandsmart™ feature continuously monitors the load on the drum motor to prevent an overload situation. The mirrored design of the dust hood optimizes dust collection preventing chips and dust from getting between your work-piece and the finish. The JET JWDS-2550 Drum Sander delivers everything you need for an effortless finish.

FEATURES

- Conveyor bed parallelism is easily adjusted by turning the dial on the outside of the bed - no tools required
- Drum is easily removable
- Drum utilizes sealed and permanently lubricated ball bearings for longer life
- Dust hood includes an integrated channel that mirrors the shape of the drum and directs chips and dust to the 4" collection port
- Dust hose hanger for added ease of use
- Infinitely variable speed control of up to 10 feet per minute allows the user to choose the optimal feed rate
- Integrated on/off switch and variable speed control knob are conveniently located
- Parallelism adjust dial features a stop to quickly return the conveyor bed to a flat position
- Precision-flattened reinforced steel conveyor bed
- Precision-machined and dynamically balanced extruded aluminum drum is designed to dissipate heat and protect the work surface from heat-damage
- Sandsmart™ control continuously monitors the load on the drum motor and automatically regulates the speed of the conveyor motor to maintain the highest feed rate without overload
- Separate feed and drum motors provide independent control, optimizing the performance of the sander
- Stand features a 24" x 50" footprint to increase stability and has a storage shelf and pre-drilled holes for casters
- The relative depth scale on the handwheel allows the user to reset and measure the depth for every project



JET RED ASSURANCE 5-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE



JWDS-2550 DRUM SANDER WITH OPEN STAND

723550OSK

SPECIFICATIONS

Drum Length (In.)	25
Style (Type)	Floorstanding Model
Drum Diameter (In.)	5
Maximum Board Thickness (In.)	4
Minimum Board Length (In.)	2-3/8
Minimum Board Thickness (In.)	1/32
Motor Power (HP)	1-3/4
Dust Port Outside Diameter (In.)	4
Motor Amps	15



STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE