



JOSS-S, FLOOR MODEL OSCILLATING SPINDLE SANDER, 1HP, 1PH, 115V


723950

Are you ready to take the hassle out of sanding? The JET Oscillating Spindle Sander is designed to deliver what you need in one fantastic machine. Featuring a spindle lock, superior dust collection and integrated storage this sander has it all. Experience a machine, and results, that are Polished At Every Angle.



FEATURES

- 1-1/2" Oscillating action reduces friction heat to protect wood and prolong sleeve life
- 4" dust port connects to your dust collection system to keep your work area clean
- Baffles create a chamber under the table for improved dust collection
- Includes 1/4", 3/8", 1/2", 5/8", 3/4", 1", 1-1/2", 2", 3" and 4" spindle assemblies
- Integrated paddle switch with safety key
- Integrated storage provides designated slots for spindles and table inserts
- Main spindle support runs on precision ball bearings and is oscillated by a heavy-duty worm and gear mechanism for consistent performance
- Powerful 1HP motor is independently mounted inside the base for easy access and service
- Sealed access door minimizes dust in the storage area
- Spindle lock for quick and easy spindle changes
- Spindles have threaded ends for quick, easy changes
- Table tilts 45° front and 15° back and features a 90° quick index
- Worm and gear mechanism runs in an oil bath to prolong its life and durability



JET RED ASSURANCE 5-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE



JOSS-S, FLOOR MODEL OSCILLATING SPINDLE SANDER, 1HP, 1PH, 115V

723950

SPECIFICATIONS

Spindle Speed (RPM)	1720
Oscillations Per Minute	75
Table Size (L x W) (In.)	24-1/2 x 24-1/2
Motor Power (HP)	1
Table Height from Floor (In.)	39-3/16
Dust Collection Minimum CFM Required (CFM)	300
Dust Port Outside Diameter (In.)	4
Motor Phase	1
Prewired Voltage (V.)	115
Motor Amps	11/5.5



STAND BEHIND YOUR WORK

550+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERVICE