PCL-18B-6

BP BendPak

Mobile Column Lifts

108,000-lb. Capacity / Mobile Column Lift System / SET OF 6

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363 Monday - Friday, 7AM to 4:30PM PST

Set of 6 Mobile Column Lifts

With 6 mobile column lifts in a single setup, you have the ability to lift up to 108,000 lbs. Despite so much lifting power, each column is easy to stow away in minutes flat after the vehicle is lowered. All lifts will be connected via a single control panel and can be stopped simultaneously with the push of a button.

Mobile Column Lift Series

LOW VOLTAGE - 208-230/190V, 50/60HZ, 3-Ph

| SKU# | Model | Description |
|---------|-----------|--------------------------------|
| 5175291 | PCL-18B-2 | 36,000-lb Capacity / SET OF 2 |
| 5175292 | PCL-18B-4 | 72,000-lb Capacity / SET OF 4 |
| 5175293 | PCL-18B-6 | 108,000-lb Capacity / SET OF 6 |
| 5175294 | PCL-18B-8 | 144,000-lb Capacity / SET OF 8 |

HIGH VOLTAGE - 460/380V, 50/60HZ, 3-Ph

| SKU# | Model | Description |
|---------|-----------|--------------------------------|
| 5175295 | PCL-18B-2 | 36,000-lb Capacity / SET OF 2 |
| 5175296 | PCL-18B-4 | 72,000-lb Capacity / SET OF 4 |
| 5175297 | PCL-18B-6 | 108,000-lb Capacity / SET OF 6 |
| 5175298 | PCL-18B-8 | 144,000-lb Capacity / SET OF 8 |



Features

- 18,000-lb. individual column capacity / 144,000-lb. maximum system capacity
- Meets or exceeds the standards prescribed by ANSI/ALI ALCTV-2017
- Just three 30' cables are used leaving the front or back of the lift clear of cable obstructions
- Intuitive controls allow the lift to be fully programmed and controlled from any column
- Smart electronics feature self-diagnostics and selfcalibration functions
- Sealed and enclosed linear potentiometers feature precision potentiometric output and high-frequency response for precise synchronization and communication of all columns through all cycles for precise, level lifting
- Height settings can be programmed for low ceiling shops









Specifications



Each Column

| Model | PCL-18B |
|------------------------------|------------------------|
| Lifting Capacity | 18,000 lbs. (8,165 kg) |
| A - Overall Height (RAISED) | 101" (2,565 mm) |
| B - Overall Height (LOWERED) | 146.5" (3,721 mm) |
| C - Max. Lifting Height | 71.5" (1,889 mm) |
| D - Overall Depth | 48.75" (1,238 mm) |
| E - Overall Width | 45" (1,143 mm) |
| F - Chassis Length | 32.25" (819 mm) |
| G - Min. Lifting Fork Width | 9.5" (241 mm) |
| H - Max. Lifting Fork Width | 35" (889 mm) |
| l - Lifting Fork Length | 11.5" (292 mm) |
| Turning Circle | 40" (1,016 mm) |
| Column Weight | 1,450 lbs. (657 kg) |
| Lifting Speed | 85 sec |
| Shipping Weight | 1,450 lbs. (657 kg) |

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for a complete list or contact BendPak via contact@bendpak.com.



