

Professional grade swing arm tire changers for OEM and oversized tires and custom wheel applications. Features an optional high-performance Bead Press System (BPS) which is highly recommended to easily aid in the servicing of low-profile, run flat, on/off road tires and commercial light trucks with stiff sidewalls and difficult rims with deep drop centers.





# SV1628BPS



Two Stage Inflation

High Torque Motor

**®** Bead Breaker Shovel

Bead Pressing System (BPS)



Polymer Mounting Head

## **Standard Accessories**



**Bead Lifting Lever** 511242



**Bead Lifting Lever Cover** C00A000017



Clamp Extensions 100012100



Clamp Cover



Nylon Mount Head w/ Hardware



Nylon Mount Head



Centering Cone Extension Z063903100



**Centering Cones** 



Hand Free Clamp



Bead Breaker Cover

220V, 1ph, L6-20P

145 psi (10 bar)



Front Insert



Rear Demount Head Insert Z063906300

# **DIMENSIONS**

Max 83" (2100 mm)

Power Supply: Air Pressure: Rim Diameter (Ext.): Tire Diameter: Max. Wheel Width:

12" - 26" 44" (1118 mm) 16" (406 mm) **Turn Table Speed:** 8-15 rpm **Shipping Weight:** 630 lbs (286 Kg)

### CONTACT



CEMB USA - BL Systems Inc. 2873 Ramsey Road, Gainesville, GA 30501 (678) 717-1050 - sales@cemb-usa.com www.cemb-usa.com





