

TWO POST GENERAL PURPOSE LIFTS

# 10K



EELR731A  
Shown with optional  
accessory 3" stack extension



10K



TWO POST GENERAL PURPOSE LIFTS

## HEAVY LOAD-LIFTING IS MADE EASIER WITH THE HOFMANN® 10K TWO POST LIFT

Hofmann® 10k Two Post automotive/general purpose lifts are packed with premium features: industrial-strength columns, low-friction lift carriage slides, low-wear components with plated arm pins, steel pulleys and more. Vehicles can be positioned and lifted symmetrically or asymmetrically.

### THREE STAGE FRONT ARMS

- Provides versatile vehicle positioning for symmetric/asymmetric lifting

### VERSATILE POWER COLUMN PLACEMENT

- Power column can be arranged on either the driver or passenger side at the time of installation

### SINGLE POINT LOCK RELEASE

- Single point, mechanical lock release allow the technician to disengage both columns simultaneously

### SCREW PADS

- Double telescoping lifting pads minimize the need for truck adapters by meeting a wider range of OEM recommended pick up points

### OVERHEAD SHUT OFF

- The padded overhead shut off system prevents vehicle damage from being raised too high

### ADJUSTABLE COLUMN HEIGHT

- Adjustable column height accommodates higher profile vehicles and provides maximum headroom to work underneath vehicles

### ANSI/ALI ALCTV:2017

- Independently tested and validated, ALI Certified to the current automotive lift standard

### AVAILABLE MODELS

10k Two Post	EELR731A
--------------	----------

### TECHNICAL SPECIFICATIONS

Capacity	10,000 lbs. (4,536 kg)
Rise height*	77.75" (200 cm)
Overall height - adjustable	147.5"/137.5" (375-350 cm)
Overall width	131.75" (335 cm)
Drive thru width	98.375" (250 cm)
Floor to overhead shut off	140.5"/130.5" (357/331 cm)
Three stage front arm reach	21.75" to 39.25" (55-100 cm)
Rear arm reach	38.25" to 55.375" (97-141 cm)
Lowered pad height	4.25" to 6.75" (11-17 cm)
Width between columns	110.25" (280 cm)
Rise time	52 s
Power requirements**	208-230V, 1Ph, 60Hz
Max load per arm	2,500 lbs (1,134 kg)

### OPTIONAL ACCESSORIES

Extension Adapter Kit Includes: • 3" stack extensions (4) • 6" stack extensions (2) • organizer brackets w/mounting hardware	EAK0299T22A
6" stack adapter extensions (2)	EAK0299T23A
Air/Electric Workstation w/filter, lubrication, regulator	EAK0299T27A
U-shaped frame truck adapters (4)***	EAK0299T25A
U-shaped frame truck adapters (2)***	EAK0299T24A
24" blue height extension	EAK0299T26A
Adapter Kit Includes: EAK0299T22A and EAK0299T25A	EAK0299T29A
Truck Footpad (2)	B2280PR
Electric Vehicle Footpad (4)	TFPK

\*Rise height is measured with screw pad adjusted to maximum height

\*\*Optional three phase electrical also available, specify at time of order

\*\*\*Frame engaging adapters (EAK099T24A or EAK0200T25A) are required when lifting vehicles w/ frame construction

For more information regarding the 10k Two Post Lift, call 800.251.4500 (US) or 501.505.2662 (Canada) [www.hofmann-equipment.com](http://www.hofmann-equipment.com)

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2021 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 01/2021 SS143385B

