

GENERAL PURPOSE TIRE CHANGER

monty<sup>®</sup>

TIRE CHANGING SYSTEMS

1270



HOFMANN<sup>®</sup> 

# 1270



## INNOVATIVE TIRE CHANGER FOR GENERAL REPAIR SHOPS

Swing-arm tire changer with small footprint and 20" outside clamping capability

### KEY FEATURES

- Strong rugged design ensures long service life
- Mounting arm swings to the side allowing space saving installation directly against a wall
- Double acting bead breaker cylinder allows precise handling of rims
- Large anti-skid rubber protective pad on bead breaker head protects tires and rims
- Plastic protectors on mount/demount head protects delicate alloy rims
- Mount/demount head is manually adjusted for non-rim contact operation
- Tire lever included

MONTY® TIRE CHANGING SYSTEMS

### AVAILABLE MODELS

monty 1270 EEWH764AU1

### TECHNICAL SPECIFICATIONS

Inner clamping range	12" - 22" (30.5 - 55.9 cm)
Outer clamping range	10" - 20" (25.4 - 50.8 cm)
Rim width	3" - 12" (7.6 - 30.5 cm)
Maximum tire width	13" (33 cm)
Maximum wheel diameter	39" (100 cm)
Speed	7 rpm
Bead breaking range	3" - 13" (7 - 34 cm)
Compressed air supply	115 - 175 PSI (8 - 12 BAR)
Dimensions (W x D x H)	45.3"x40.6"x68" (115x103x173 cm)
Weight	381.4 lbs (173 kg)
Power supply	115V 1Ph 50/60Hz

### OPTIONAL ACCESSORIES



EAA0304G52A - Plastic rim protector set



EAA0304G36A - Quick exchange device



EAA0304G15A - Protector bead breaker shovel



EAA0247G20A - Plastic mounting head

For more information regarding the monty® 1270, call 800.251.4500 (US) or 501.505.2662 (Canada) [www.hofmann-equipment.com](http://www.hofmann-equipment.com)

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2018 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders.

11/18 SS163543A

