

# UNCOMPROMISING FEATURES IN A COMPACT DESIGN

Introducing the latest addition to the Hofmann® Imaging Alignment family – the geoliner® 609 has all the same core features of our advanced imaging alignment systems in a compact, economical design. Ready out of the box with minimal installation, this alignment system offers a greater lift compatibility with an taller vertical post and two-wheel elevated compensation mode - making the *geoliner* 609 a flexible alignment solution to support in-house alignment services.

TECHN	Irol	CDE	PIEIP	ATIONS
	пап	- OF E	all lla	

Part Number	EEWA741TH3
Wheel Size	12"-24"   305-610mm
Track Width	48"-96"   1219-2438mm
Wheelbase	79"-180"   2007-4572mm
Power Requirements	110-230 VAC 1Ph 50/60Hz 15A

## STANDARD ACCESSORIES

- · AC200 Wheel Clamps & Targets
- · Brake Pedal Depressor
- · Tablet Display with Case
- **OPTIONAL ACCESSORIES**
- · Mobility Kit
- 4" Clamp Extension Kit
- 2" Wheel Hub Extension
- · Pointer Target

- · Steering Wheel Holder
- · Wheel Chocks
- · Wall-Mounted Clamp Hangers
- · Low-Profile Tire Adapter
- · Quick Clamp Kit
- Wheel Clamp Floor Stand

## VERSATILITY

- · Minimal shop space, no console needed
- · Control the aligner from anywhere in the shop using the tablet
- · Rotating camera beam for smaller storage footprint

## **EFFICIENT DESIGN**

- Pre-assembled, ready-to-install
- · Lightweight, allows one-person installation
- · Robust mechanical winch for precise camera beam movement

## INTELLIGENT SOFTWARE TOOLS

- Elevated two-wheel compensation mode for customers with limited space, no alignment lift, or vehicles too large for the lift
- Predictive alignment flow and automatic error detection system
- · Video-speed imaging for fast roll-back compensation
- VODI™ technology guides efficient measuring

## ONLINE CONNECTIVITY

- · Network updatable software and specifications
- Quick access to vehicle specifications and repair information, TSBs, recalls, TPMS, ADAS information
- · Cloud services printing





