

WHEN SAFETY DEPENDS ON PERFORMANCE!

76720B

20 Ton Capacity

Low Height

Air Operated

Hydraulic Bottle Jack

INTENDED USE

For use in heavy duty trucks, farm equipment, building construction, construction and mining equipment, mobile home set-up and oil field applications.



FEATURES

- Fast efficient air pump reduces lifting time and has a built-in relief mechanism which prevents the jack from being used beyond its maximum allowable capacity.
- Convenient push button air valve connected to an in-line filter prevents contaminates from entering the air/hydraulic system.
- Unique design allows for manual operation when air is not available.
- Two piece zinc plated handle.
- Parkerized coating on pump piston, extension screw and extension adapters and chrome coated ram offer protection against rust.
- Longer wear life due to internally machined oil passages, smooth bearing surfaces and close tolerances.
- Safety bypass and overload systems prevent cylinder damage and prevent the jack from being used beyond the ASME/PASE load-limiting standard.
- Carrying handle.

MODEL	LIFT HEIGHT			SCREW			P.S.I.	SHIPPING
NUMBER	CAPACITY	Low	High	STROKE	EXTENSION	BASE SIZE	RANGE	WEIGHT
76720B	20 Ton	8.25"	14.5"	4"	2.25"	6.44" x 9"	100-130	36 lbs.