

WHEN SAFETY DEPENDS ON PERFORMANCE!



8 1/2 Ton Capacity Long Reach Air Lift Jack

INTENDED USE

For truck, bus, farm equipment and motor home applications where a long reach jack is required to lift at the vehicle bumper, frame or front axle.



FEATURES

- Three-way heavy duty air valve provides fine control when lifting or lowering a vehicle.
- Automatic safety lock engages in five different height positions independent of air pressure.
- Includes extension tubes and adjustment pins for added height requirements.
- Two 10" diameter solid wheels are strategically located for better positioning and maneuverability.
- Scissors action frame design with four 5" diameter steel wheels provides maximum stability during lifting and lowering.
- Large air cylinder requires only 100 p.s.i. air pressure to lift 5 ton capacity.
- Over four feet of reach between cylinder and center line of lifting saddle.

MODEL		LIFT HEIGHT		OVERALL DIMENSIONS			SADDLE	SHIPPING
NUMBER	CAPACITY	Low	High	Length	Width	Height	REACH	WEIGHT
82995	5 Ton @ 100 P.S.I. 7 Ton @ 150 P.S.I. 8-1/2 Ton @ 180 P.S.I.	10"	50"	80.5"	38"	53.75"	50"	935 lbs.