



PROFESSIONAL LIFTING EQUIPMENT

WHEN SAFETY DEPENDS ON PERFORMANCE!

925011

**200 / 10,000 P.S.I.
Two-Speed
Lightweight Hand Pump**

925012A

**10,000 P.S.I.
Single-Speed
Lightweight Hand Pump**

INTENDED USE

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity.



FEATURES

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.
- External load release valve for single-acting cylinder operation.
- Two-speed pump operation (Model 925011 only) reduces handle strokes by as much as 78% over single speed pumps.
- Durable glass-filled nylon reservoir and nylon encapsulated aluminum pump base for maximum corrosion resistance and lightweight handling.
- Handle lock for easy carrying.
- Non-conductive fiberglass handle for operator safety.

| PUMP TYPE | | | | MODEL NUMBER | PRESSURE RATING (P.S.I.) | | USABLE OIL CAP. (Cu. In.) | OIL DISPLACEMENT PER STROKE (Cu. In.) | | MAXIMUM HANDLE EFFORT (Lbs.) | PISTON STROKE (in.) | DIMENSIONS (Inches) | | | PUMP HANDLE ARC | WEIGHT (Lbs.) |
|--------------|-----------|-------|--------------|--------------|--------------------------|------------|---------------------------|---------------------------------------|------------|------------------------------|---------------------|---------------------|-------|--------|-----------------|---------------|
| Single Speed | Two Speed | Steel | Light Weight | | 1st. Stage | 2nd. Stage | | 1st. Stage | 2nd. Stage | | | Length | Width | Height | | |
| ● | | ● | | 925009A | 2,850 | — | 18 | .16 | — | 57 | .81 | 13.38 | 5.25 | 5.25 | 40° | 11 |
| ● | | ● | | 925010A | 10,000 | — | 40 | .16 | — | 111 | .81 | 23 | 5.25 | 5.25 | 40° | 13 |
| | ● | | ● | 925011 | 200 | 10,000 | 55 | .687 | .151 | 93 | 1.00 | 21.63 | 4.75 | 7 | 50° | 9 |
| ● | | | ● | 925012A | 10,000 | — | 55 | .151 | — | 85 | 1.00 | 21.63 | 4.75 | 7 | 50° | 9 |
| | ● | ● | | 925013B | 350 | 10,000 | 134 | .99 | .15 | 104 | 1.00 | 22.5 | 5.75 | 7 | 50° | 24 |
| | ● | | ● | 925014 | 400 | 10,000 | 155 | 2.40 | .151 | 95 | 1.00 | 21.75 | 4.75 | 9 | 50° | 22 |