

CEMB[®] USA



SM825EVO PA

A traditional swing arm tire changer and great place to start for general service of the majority of OEM fitments and many custom tires and wheels. These durable machines are equipped with basic features, intended for mid-volume use.

SM825EVO PA

☛ Table Top Clamping

☛ Two Stage Inflation

☛ High Torque Motor

☛ Bead Breaker Shovel

☛ High Performance Press Arm

☛ Polymer Mounting Head



Standard Accessories



Bead Lifting Lever
511242



Bead Lifting Lever Cover
C00A000017



Clamp Cover
YC130001468




Bead Breaker Cover
YC13013240



Rear Inserts
YC13013650

Front Inserts
YC13006689

DIMENSIONS



Power Supply: 110V, 1ph or Air
Air Pressure: 145 psi (10 bar)
Rim Diameter (Ext.): 12" - 24"
Tire Diameter: 44" (1118 mm)
Max. Wheel Width: 15" (381 mm)
Turn Table Speed: 8-15 rpm
Shipping Weight: 630 lbs (286 Kg)

CONTACT

CEMB[®] USA

CEMB USA - BL Systems Inc.
2873 Ramsey Road, Gainesville, GA 30501
(678) 717-1050 - sales@cemb-usa.com
www.cemb-usa.com

(678) 717-1050 • www.cemb-usa.com • 2873 Ramsey Road, Gainesville, Georgia

