

## FEATURES

- Provides 1,450 ft-lb maximum torque and 1,700 ft-lb of loosening torque
- VIBROTHERM DRIVE® impact wrenches incorporates the new patented AIRCAT design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels
- The patented grip design provides the customary AIRCAT operator comfort
- Investment in tooling, materials, and the triple injection molding processes enables AIRCAT® to produce cosmetic designs that are unmatched in the industry

## SPECIFICATIONS

Length (in.)	7.4
Width (in.)	3.6
Height (in.)	8.4
Weight (lbs.)	7.4
Bolt Capacity (in.)	1
Loosening Torque (ft-lbs)	1700
Working Torque (ft-lb)	220-1015
Air Cons. (CFM)	8
Rec. Hose Size (in.)	1/2
Air Inlet (in.) NPT/BSP	3/8 NPT
Vibration Level (m/sec <sup>2</sup> )	6.5
Noise Level d(B)A	86



Styled for perfection  
and built to last!

Square Drive (in.)	3/4
Free Speed (RPM)	5400
Impacts Per Minute (IPM)	1300
Max. Torque (ft-lb)	1450

**AIRCAT**

a Division of Florida Pneumatic Manufacturing Corporation  
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

[www.AIRCAT.com](http://www.AIRCAT.com)

**(800) 356-3392**