

CHAIN-DRIVE 30-60K 44030, 44040, 44050, 44060

From 30,000-60,000 lbs. capacity, Challenger's heavy-duty, chain-driven 4-Post Lifts accommodate a wide range of heavier vehicles. Broaden your revenue potential by expanding into the fleet and commercial truck and transit service. Take your heavy-duty vehicle service to the next level.



MODEL NUMBER	44030 / E / EAR / X	44040 / E / X	44050 / E / X	44060 / X
Lifting Capacity	30,000 lbs.	40,000 lbs.	50,000 lbs.	60,000 lbs.
Overall Length (A)	24' 7.5" / 29 7.5" / 29 7.5" / 34' 7.5"	36' / 41' / 46'	36' / 41' / 46'	36' / 41' / 46'
Overall Width (B)	12' 5.5"	17' 1.25"	17' 1.25"	17' 1.25"
Inside Columns (C)	132.5"	144"	144"	144"
Between Columns (D)	233.75" / 293.75" / 293.75" / 353.75"	290" / 350" / 410"	290" / 350" / 410"	290" / 350" / 410"
Overall Height (E)	92"	92"	92"	92"
Height of Runways (F)	9"	14"	14"	14"
Width of Runways (G)	24"	32"	32"	32"
Width Between Runways (H)	54" - 75"	36" - 58"	36" - 58"	36" - 58"
Max Wheelbase (I)	230" / 290" / 290" / 350"	310" / 370" / 430"	310" / 370" / 430"	310" / 370" / 430"
Rise Height (J)	68"	73"	73"	73"
Max. 2-Wheel Alignment	NA / NA / 266" / NA	NA	NA	NA
Standard Motor / Voltage	3HP, 208-230v, 1pH, 30a	10HP, 230-460v, 3pH, 30a	15HP, 230-460v, 3pH, 30a	15HP, 230-460v, 3pH, 30a
Rise Time	105 s	70 s	75 s	75 s
Concrete Specifications	4" Thick, Reinforced, Free from cracks/seams, rated at 3500+ psi and cured at least 28 days			

