

ABOVEGROUND

USED OIL STORAGE SYSTEMS

Used oil evacuation, storage and transfer is safer, cleaner and faster with a pump-assist system from JohnDow Industries. Ideal for new car dealers, tire and automotive service stores and dealers, heavy-duty fleet owners and operators, and municipal garages, these used oil storage systems are perfect for daily use.





Features include:

- UL Listed double-wall tank provides 110% secondary containment
- Meets UL 142 specifications as well as the requirements of Uniform Fire Code and NFPA 30
- Workbench style tanks in 180-, 285and 500-gallon capacities
- Vertical-style for space saving is available in a 245-gallon capacity
- UL Listed, 1" air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shut-off to prevent overfilling
- 3/4" x 10' suction hose with quickconnect coupler
- 2" drop tube with camlock fitting and dust cover
- Air filter regulator
- Easy-to-read level gauge
- High gloss enamel finish
- Protective cover for pump and shut-off valve

SPECIFICATIONS:	AGS-180D	AGS-245D	AGS-285D	AGS-500D
STYLE	WORKBENCH	VERTICAL	Workbench	Workbench
CAPACITY (GAL.)	180	245	285	500
DIMENSIONS (L x W x H)	56" x 28" x 40"	40" x 37-1/2" x 69"	67" x 31" x 41"	89" x 49" x 40"
WEIGHT	725 LBS.	1 1 00 LBS.	1 1 00 LBS.	1 300 LBS.

151 SNYDER AVE. | BARBERTON,OH 44203 | TOLL-FREE: 800.4330708 | FAX: 330.753.6419



FLUID EVACUATORS

Applications include:

- Traditional automotive repair -Including oil, coolant, transmission fluid, brake fluid, differential oil, and power steering fluid.
- Auto Dealers Essential for European manufactured vehicles that do not include a factory drain plug (Audi, VW, Mercedes Benz, Land Rover, Jaguar).
- Quick Lubes Avoid stripped drain plugs. Makes it easy to correct overfills.
- Motorcycle/ATV Service Perfect for oil changes.
- Marine Applications Boats, Jet Skis, and other PWC.
- Farm & Industrial Tractors, generators, off-road equipment.



JDI-20EV-B

20-Gallon Fluid Evacuator with Transparent Bowl

The JDI-20EV-B is equipped with a 2-gallon transparent bowl which gives the operator the option to check quantity and quality of oil prior to discharging it into the tank below. The bowl is heat-resistant to a maximum of 212°F.







Probes & AdaptersEvacuators come with six suction probes and three "OE Style" adapters.