

GALLON UL LISTED STEEL GAS CADDIES



Features include:

- 30-gallon capacity steel tank
- UL Listed and complies with OSHA guidelines
- Fill level gauge
- Internal filter system
- 4-way directional valve
- Heavy-duty locking rear wheels and locking front casters
- Ground wire and clamp
- 8' PVC suction/ discharge hose with internal grounding wire
- Decal set for contents identification

STEEL & CADDIES

WITH MANUAL OR AIR OPERATED PUMP

Pumps available on the PRO30 Gas Caddies

FC-P30-UL



UL Listed Two-Way Rotary Pump

This heavy-duty UL listed pump features carbon vanes and Viton seals. The 2-way operation allows for either siphoning or dispensing fuel. One gallon is delivered for every 12 turns of the pump handle.

FC-P30A-UL



UL Listed Air Diaphragm Pump

Designed for efficiency and productivity, this air diaphragm pump quickly and quietly pumps fuel to and from the vehicle by connecting shop air to the air throttle control on the top of the tank.

SPECIFICATIONS:	FC-P30-UL	FC-P30A-UL
GALLONS	30-gallon	30-gallon
MATERIAL	STEEL	STEEL
Риме	TWO-WAY MANUAL	UL LISTED AIR OPERATED
WHEEL SIZE – FRONT	5" LOCKING SWIVEL CASTERS	5" LOCKING SWIVEL CASTERS
WHEEL SIZE - REAR	1□" HEAVY-DUTY FIXED	1 " HEAVY-DUTY FIXED
FILTER	1 O MICRON	10 MICRON
DIMENSIONS	24" W x 30" L x 41" H	24" W x 30" L x 41" H
WEIGHT	165 LBS.	165 LBS.

Other features:



4-Way Valve

An integral 4-way valve clearly directs the flow of fuel to and from the vehicle.



Integral Filter System

To protect vehicle fuel pumps from contamination, this gas caddy comes equipped with an in-line system that filters the fuel in both directions. A 10 micron filter is include and replacement filters are available in 1. 10 and 30 microns.



Vent and Level Gauge

The level gauge provides a quick look at the tank fluid level while the vent prevents excess build-up of fumes.



Fill Spout

Quickly add fuel to the caddy tank using easy-access fill spout.

151 SNYDER AVE. | BARBERTON,OH 44203 | TOLL-FREE: 800-4330708 | FAX: 330-753-6419

