



CEMB[®] **USA**
WHEEL SERVICE EQUIPMENT

CM27T

The CM27T is perfectly suited for tube and tubeless types of tires used on over-the-road Class 8 commercial trucks and some off-road tractor tires and rims. The pivoting four jaw clamping chuck aids as a wheel lift. Prevents liabilities of manual truck tire changing by allowing the machine to perform all the heavy lifting and service work.

- Portable Control Unit**
- Bi-Directional Clamping**
- Adjustable Bead Loosening Roller**
- Heavy Duty Truck & Bus**
- Pivoting Four-Jaw Clamping**
- Self-Centering Wheel Clamping**



STANDARD MANUAL ACCESSORIES

Bead Lifting Lever



Bead Lifting Guide Lever



Alloy Rim Pliers



DIMENSIONS

Power Supply:	220V, 1ph, L6-20p
Air Pressure:	0-1885 psi (0-130 bar)
Max. Rim Diameter:	27"
Max. Tire Diameter:	63"
Max. Wheel Width:	30"
Bead Breaker Force:	4100 lbs. (1860 Kg)
Shipping Weight:	1415 lbs. (640 Kg)



CEMB[®] **USA**
WHEEL SERVICE EQUIPMENT

678-717-1050

www.cemb-usa.com