



**CEMB**<sup>®</sup> **USA**  
WHEEL SERVICE EQUIPMENT

# SM56T

A heavy-duty off road tractor tire changer with wheel clamping range from 14"-46" maximum tire diameter of 90" and maximum tire width of 42". Perfectly suited for tube and tubeless tires used on heavier off road farm and commercial use tractors.

- Portable Control Unit**
- Bi-Directional Clamping**
- Adjustable Bead Loosening Roller**
- Farm & Commercial Tractors**
- Pivoting Four-Jaw Clamping**
- Self-Centering Wheel Clamping**



## STANDARD MANUAL ACCESSORIES

**Bead Lifting Lever**



**Bead Lifting Guide Lever**



**Alloy Rim Pliers**



## DIMENSIONS

<b>Power Supply:</b>	220V, 1ph, L6-20p
<b>Air Pressure:</b>	0-1885 psi (0-130 bar)
<b>Max. Rim Diameter:</b>	27"
<b>Max. Tire Diameter:</b>	63"
<b>Max. Wheel Width:</b>	30"
<b>Bead Breaker Force:</b>	4100 lbs. (1860 Kg)
<b>Shipping Weight:</b>	1415 lbs. (640 Kg)



**CEMB**<sup>®</sup> **USA**  
WHEEL SERVICE EQUIPMENT

678-717-1050

[www.cemb-usa.com](http://www.cemb-usa.com)