



CEMB[®] USA
WHEEL SERVICE EQUIPMENT

SM628BPS

Professional grade swing arm tire changers for OEM and oversized tires and custom wheel applications. Features an optional high-performance Bead Press System (BPS) which is highly recommended to easily aid in the servicing of low-profile, run flat, on/off road tires and commercial light trucks with stiff sidewalls and difficult rims with deep drop centers.



- Table Top Clamping**
- High Torque Motor**
- Bead Pressing System**
- Two Stage Inflation**
- Bead Breaker Shovel**
- Polymer Mounting Head**

STANDARD MANUAL ACCESSORIES


Bead Lifting Lever



Bead Lifting Lever Cover



Clamp Extensions



Clamp Cover



Nylon Mount Head w/ Hardware



Nylon Mount Head



Centering Cone Extension



Centering Cones



Hand Free Clamp



Bead Breaker Cover



Front Insert



Rear Demount Head Insert



DIMENSIONS

Power Supply:	220V, 1ph, L6-20P
Air Pressure:	145 psi
Max. Rim Diameter:	26"
Max. Wheel Width:	16"
Max. Tire Diameter:	44" (914 mm)
Turn Table Speed:	8-15 rpm
Shipping Weight:	630 bs. (286 kg)



CEMB[®] USA
WHEEL SERVICE EQUIPMENT

678-717-1050

www.cemb-usa.com