



**CEMB**<sup>®</sup> U S A  
WHEEL SERVICE EQUIPMENT

# SM645HP2

Professional quality automatic locking tilt-column tire changer features HP2 high performance press arm highly recommended to easily aid in the servicing of high performance and run flat tires with stiff sidewalls and difficult wheels with deep drop centers.

- Self-Centering Turntable**
- Automatic Tilt-back**
- Bead Loosening System**
- Side Shovel**
- Two Stage Inflation**
- HP2 Side Presser Arm**



## STANDARD MANUAL ACCESSORIES

**Bead Lifting Lever**



**Bead Lifting Lever Cover**



**Rear Inserts**



**Front Inserts**



**Clamp Cover**



**Bead Breaker Cover**



## DIMENSIONS

- Power Supply:** 110V, 1ph
- Air Pressure:** 115-145 psi (8-10 bar)
- Max. Rim Diameter:** 26" (661 mm)
- Max. Rim Width:** 13" (380 mm)
- Max. Tire Diameter:** 44" (1118 mm)
- Turn Table Speed:** 8-15 rpm
- Shipping Weight:** 950 lbs. (431 kg)



**CEMB**<sup>®</sup> U S A  
WHEEL SERVICE EQUIPMENT

678-717-1050

[www.cemb-usa.com](http://www.cemb-usa.com)