

## 30K 4-POST / ALIGNMENT 4030 SERIES

With general service or alignment versions and three length options, our 30,000 lbs. HD 4-Post is no understatement. The cable and cylinder system with steel sheaves make up this lift's HD design and provides durability. **Non-skid louvered approach ramps and a built-in runway rail system bring versatility to any workspace.**

### SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 12' minimum
-  **WIDTH:** 17' recommended
-  **DEPTH:** 28' recommended
-  **POWER:** 208-230v, 1pH, 30a
-  **AIR:** 90-120 psi

**CONCRETE**  
4" thick, reinforced, free from cracks/seams,  
3500+ psi & cured 28+ days



MODEL # 4030

MODEL NUMBER	4030SFX	4030EFX	4030XFX	4030SAX	4030EAX	4030XAX
Description	Standard Flat Deck	Extended Length Flat Deck	Extra Extended Length Flat Deck	Standard Alignment Deck	Extended Length Alignment Deck	Extra Extended Length Alignment Deck
Lifting Capacity	<b>30,000 lbs.</b>					
<b>Max.</b> Wheelbase	244½"	281"	317"	244½"	281"	317"
<b>Max.</b> 2-Wheel Alignment	NA			219½"	256"	292"
Rise Height	71¼"					
Overall Length	25' 8"	28' 8"	31' 8"	25' 8"	28' 8"	31' 8"
Overall Width	14' 4¾"					
Inside Columns	12' 8"					
Between Columns	20' 6"	23' 6½"	26' 6½"	20' 6"	23' 6½"	26' 6½"
Height of Columns	92¼"					
Height of Runways	10"					
Width of Runways	24"					
Width Between Runways	46" - 52"					
Air Supply Required	90-120 psi					
Standard Motor/Voltage	3HP, 208v-230v, 60Hz, 1Ph					
Rise Time	126s					
<b>Min.</b> Required Bay Size	28' x 17'	31' x 17'	34' x 17'	28' x 17'	31' x 17'	34' x 17'
ALI® Certified	<input checked="" type="checkbox"/>					
Available Colors	■					