

15K 4-POST ALIGNMENT 4115 SERIES

The 26" wide runways allow you to service or align a wide range of vehicles from small passenger cars to medium-duty trucks up to 15,000 lbs.

SERVICE BAY SPECIFICATIONS

- HEIGHT:** 78" + vehicle
- WIDTH:** 14' recommended
- DEPTH:** 24' recommended
- POWER:** 208-230v, 1pH, 30a
- AIR:** 90-120 psi

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days



PRODUCT SPECIFICATIONS

| MODEL NUMBER | 4115EFO | 4115XFO | 4115EFX | 4115XFX | AR4115EAO | AR4115XAO | AR4115EAX | AR4115XAX |
|----------------------------|---------------------------------|--|-----------------------------------|--|--------------------------------------|---|--|--|
| Description | Standard, Open-Front, Flat Deck | Extended Length, Open-Front, Flat Deck | Standard, Closed-Front, Flat Deck | Extended Length, Closed-Front, Flat Deck | Standard, Open-Front, Alignment Deck | Extended Length, Open-Front, Alignment Deck | Standard, Closed-Front, Alignment Deck | Extended, Closed-Front, Alignment Deck |
| Lifting Capacity | 15,000 lbs. | | | | | | | |
| Open or Closed Front | Open | | Closed | | Open | | Closed | |
| Max. Wheelbase (I) | 183" | 210½" | 183" | 210½" | 183" | 210½" | 183" | 210½" |
| Max. 2-Wheel Alignment (J) | NA | | NA | | 167¾" | 195½" | 167¾" | 195½" |
| Max. 4-Wheel Alignment (K) | NA | | NA | | 68" - 158" | | | |
| Rise Height (L) | 78" | | | | | | | |
| Overall Length (A) | 20' 10¾" | 23' 1" | 20' 7½" | 22' 11½" | 20' 10¾" | 23' 1" | 20' 7½" | 22' 11½" |
| Overall Width (B) | Front: 142" Rear: 141¾" | | 141¾" | | Front: 142" Rear: 141¾" | | 141¾" | |
| Inside Columns (C) | Front: 120¾" Rear: 125½" | | 125½" | | Front: 120¾" Rear: 125½" | | 125½" | |
| Between Columns (D) | 195" | 222½" | 196¾" | 223¾" | 195" | 222½" | 196¾" | 223¾" |
| Height of Columns (E) | Front: 99¼" Rear: 98" | | 98" | | Front: 99¼" Rear: 98" | | 98" | |
| Width of Runways (G) | 26" | | | | | | | |
| Height of Runways (F) | 7" | | | | | | | |
| Width Between Runways | 40½" | | | | | | | |
| Air Supply Required | 90-120 psi | | | | | | | |
| Standard Motor/Voltage* | 3HP, 208v-230v, 60Hz, 1Ph | | | | | | | |
| Rise Time | 85s | | | | | | | |
| Required Bay Size W x L | 14' x 24' | 14' x 26' | 14' x 24' | 14' x 26' | 14' x 24' | 14' x 26' | 14' x 24' | 14' x 26' |
| AII® Certified | ☑ | | | | | | | |