TWO-POST

HEAVY-DUTY LIFTS

AMGO's latest OH-18 boasts heavy-duty construction, offering immense lifting capacity up to 18000lbs. It features long, sturdy carriages for enhanced stability and is equipped with two types of rubber pads to suit various vehicles. Moreover, it incorporates AMGO's 3 in 1 technology for effortless height setting.



TWO POST LIFT

Main Features

- √ 18,000 Lbs capacity.
- √ Clearfloor design, provide unobstructed floor space.
- √ Overhead safety shut-off device.
- √ Munual single-point safety release, unlock both columns from 1 side.
- √ Automatic arms restraints.
- √ Aero sync cables incorporate AMGO 3 in 1 technology.
- √ Dual hydraulic direct-drived cylinders, designed and made on high standard, high quality seals for cylinder.
- √ Standard two-stage rugged arms to ensure the heavy load stability.
- √ Equipped with long, sturdy carriages for enhanced stablity.
- √ Both standard rubber pads and heavy duty saddle adapters come as standard.
- √ Available with 3 heights settings.



Single point safety release makes it easier for operators to unlock both columns from



Hydraulic Direct-drived Cylinders.



Both stackable rubber pads and heavy duty saddle adapter are include as standard.



1.5", 2.5", and 5" extension adapters are included as standard.




Automatic arm restraints



Equipped with extremely long carriages to enhance the stability.

SPECIFICATIONS



| Model | | OH-18 |
|--|---|---------------------------------------|
| Lifting Capacity | | 18,000 lbs |
| Lifting Time | | 84s |
| Max. Lifting height: (w/o extension adapter) | Α | 75 1/4" |
| Max. Lifting height: (w/ extension adapter) | | 81 1/4" |
| Max. lock height: (w/o extension adapter) | | 73 5/16" |
| Max. lock height: (w/ extension adapter) | | 82 5/16" |
| Overall Height:(low setting) | | 174" |
| Overall Height:(Medium setting) | В | 186" |
| Overall Height:(High setting) | | 198" |
| Overall Width | С | 150 3/4" |
| Drive-Thru Clearance | D | 110 7/16" |
| Width Between Columns | Е | 123 1/2" |
| Minimum Pad Height | F | 7 1/4" |
| Gross | | 2,787 lbs |
| Motor | | 2.0HP,2.0HP,220V 60Hz,single phase |

AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211,USA Tel:(214)377-7742

