

12K INGROUND

EV1220

Our EV1220 can handle anything from full-sized vehicles to medium-duty trucks and SUVs, up to 12,000 lbs.



REQUIREMENTS

- 12' MINIMUM**
- 12' RECOMMENDED**
- 24' RECOMMENDED**
- 208-230V, 1PH, 30A**
- 90-120 PSI**

CONCRETE
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days

All Ingrounds are fully contained to eliminate any risk of environmental impact.

SPECIFICATIONS

MODEL NUMBER	EV1220 / EV1220-QC
Description	Standard / QuickCycle™
Lifting Capacity	12,000 lbs.
Arm Configuration	3-Stage Front & Rear
Stroke	68"
Rise Height	74"
Overall Width	115"
Drive Thru Clearance	7' 3"
Arm Reach	Min. 19⁵/₈" Max. 48"
Screw Pad Height	4 ¹ / ₂ "-6 ¹ / ₄ "
Plunger Diameter	8 ¹ / ₂ "
Standard Motor/Voltage*	2HP, 208v-230v, 60Hz, 1Ph / 3HP, 208v-230v, 60Hz, 1Ph
Rise Time	60s / 38s
Max. Load per Arm	3,000 lbs.
Required Ceiling Height	12'
ALI® Certified	<input checked="" type="checkbox"/>

SERVICE BAY LAYOUT

