

## 9K DRIVE-ON PAD LIFT CL10V3-XP9

Low-profile, drive-on style pads provide quick vehicle spotting for express service bays. Ramps flip up and lock to extend the platforms for longer wheelbases.

### SERVICE BAY SPECIFICATIONS

- HEIGHT:** 12' minimum
- WIDTH:** 14' recommended
- DEPTH:** 24' recommended
- POWER:** 208-230v, 1pH, 30a

**CONCRETE**  
4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days



MODEL # CL10V3-XP9

### PRODUCT SPECIFICATIONS

MODEL NUMBER	CL10-XP9	CL10-XP9-DPC-QC
Description	Drive-on Pad Lift	Drive-on Pad Lift, DPC & QuickCycle™
Lifting Capacity	<b>9,000 lbs.</b>	
Rise Height (A)	70"	
Height of Columns	Standard 11' 8" or 11' 2" w/ 2' or 3' extensions	
<b>Max.</b> Extended Cylinder Height	11' 11"	
Adjustable Width Overall	11' 6½" - 11' 11"	
Drive Thru Clearance	90"	
Floor to Overhead Switch	Standard 11' 2½" or 10' 8½" w/ 2' or 3' extensions	
Low Lock Height	12" Net Rise	
Platform Length	58" / 66½" / 75"	
Standard Motor/Voltage	2HP, 208v-230v, 60Hz, 1Ph	<b>3HP, 208v-230v, 60Hz, 1Ph</b>
Rise Time	38s	<b>24s</b>
<b>Max.</b> Load per Arm	NA	
Required Ceiling Height	12' Minimum	
ALI® Certified	<input checked="" type="checkbox"/>	

### SERVICE BAY LAYOUT

